


Measurement instructions: flap opening downwards

Step 1 – External dimensions:

Measure the width and height of the flap **from outer edge to outer edge** on the inner/rear side of the flap, and enter the measurements (mm) in the appropriate boxes.

Required tools:

Tape measure, pen, and the printed measurement instructions.



Step 2 – Drilling and fittings (optional):

Upon request, we can supply you with matching fittings (including drilling). You can select these in the configurator.

Next, measure how many millimetres your existing front overlaps the edges of the carcass of your cabinet.

bottom _____ mm

left _____ mm

right _____ mm

Step 3 – Handle drilling (optional):

For flaps, the handles are always positioned centrally and aligned horizontally.

If you already have your own handle that you would like to mount on your new flap, please provide us with the distance between the handle screws (in mm). This is always measured from the centre of one screw hole to the centre of the other screw hole.

Distance between handle screws: _____ mm

Step 4 – Configuration

After measuring, you can quickly and easily enter the data into the configurator at <https://www.Furnfab.com/en/renovating-fronts>.

Need help?

If you have any questions, our team is happy to assist you!

You can reach us easily and quickly by email, through our website, or by phone:

Email: service@furnfab.com

Contact form: <https://www.furnfab.com/en/contact>

Phone: +44 (0) 131 608 34 77

